

## Motorized Tugs

Imagine if the transport of heavy equipment, materials and supplies throughout your facility was not an issue.

Would that be worth it to you?

The AmericartUSA™ powered tugger is a safe and compact solution for moving heavy equipment, materials and supplies that are already on a wheeled base. With these motorized tugs, one staff member can quickly and safely perform the same task that may currently take multiple trips and staff.

Order your tug today!

Visit [www.americartusa.com](http://www.americartusa.com) and use our easy order online system!



### Smart Charging System

The AmericartUSA™ powered tugs are battery operated and equipped with a self-contained 115V smart charging system. Keep the unit plugged in whenever it is not in use.

### 1,000lb. Towing Capacity

The AmericartUSA™ powered tugs have a 1,000lb. towing capacity allowing you to safely move anything on a wheeled base that weighs up to 1,000lb.

**Order TODAY!** Available at AmericartUSA™ online | [www.americartusa.com](http://www.americartusa.com).  
Feel free to email us at [info@americartusa.com](mailto:info@americartusa.com) or give us a call at 1-877-498-0076.

## Motorized Tugs

The applications for the AmericartUSA™ motorized tuggers are virtually endless in transporting anything already on a wheeled base. These powered tugs are used to: maneuver linen carts, transport supply and food carts, handle large quantities of CO2 and air tanks, move heavy luggage or packages, deliver bulk quantities of supplies, transport deliveries from loading docks, push or pull large containers, move parts and other materials around departments, and so much more!

### Model ACTug | Motorized Tugs

#### Specifications

- Model Name and Number: ACTug
- Dimensions
  - Width: 24"
  - Length: 26"
  - Height: 40" to the top of the controller
  - Weight: 200lb.
  - Shipping Weight: 250lb.
- Turning Radius: 14"
- Towing Capacity: 1,500lb.
- Frame Construction: 10 Gauge CRS | ASTM A366
- Drive Wheel: 9" Diameter x 2" Wide
  - Grey Non-Marking
  - 4-Ply Nylon, Foam-Filled
- Caster Size: 6" Diameter x 2"
  - Performa Rubber
  - Temperature Range: -45°F to +180°F (120°F continuous service)
  - Hardness: 55 (±5) Durometer Shore A Scale
- Controller: Microprocessor-based
- Charging System
  - 120VAC
  - 2.4 A
  - Watts: 288
  - Electrical Phase: 1
  - Charging Cord: (UL) 384516 SJT 3X14AWG 105°C 300V VW-1
  - Plug Type: 5-15P
  - Drive System Voltage: 24VDC
- Battery Specifications
  - 35 AH or 55 AH Option
  - AGM Battery: Stand-By, UPS, High-Rate, Telecomm
  - Absorbed Glass Mat (AGM) - Battery
  - Synonyms: SLA, VRLA, AGM, Absorbed Glass Mat
  - Sealed Recombinant
  - Dot Description: Wet Battery, Non-Spillable
  - Chemical Name: Sealed Lead Acid, Secondary Battery
- Drive System
  - 24 VDC, 2856 RPM, 0.41 A Maximum, PMDC
  - Electromechanical Holding Brake, rated at 35.4lb./in. (4.0 Nm), with override and controller feedback
  - Top Speed: 3.40 MPH
- One Year Limited Warranty

### It's time to take on the import competition!

After designing, testing, and working out the cost structure, AmericartUSA™ was born. With more than 15 years of experience in the motorized platform cart industry, we can emphatically say that AmericartUSA™ delivers on quality (American-made standards) at a price that is competitive with all import carts.

-The AmericartUSA™ Team